

## CentOS6

/etc/rc.d/init.d/tomcat

```
#
# tomcat Start/Stop Script for the Tomcat Server
#
# chkconfig: 2345 91 14
# description: start/stop script for tomcat server

# source function library
. /etc/rc.d/init.d/functions

export LANG=ko_KR.euckr
export JAVA_HOME=/data/apps/search/java
export TOMCAT_HOME=/data/apps/search/tomcat
export LD_LIBRARY_PATH=${LD_LIBRARY_PATH}:/usr/local/glibc-2.14
export CLASSPATH="."

PRGDIR="$TOMCAT_HOME/bin"

# Check that target executable exists
if [ ! -x "$PRGDIR"/"$EXECUTABLE" ]; then
echo "Cannot find $PRGDIR/$EXECUTABLE"
echo "This file is needed to run this program"
exit 1
fi

case "$1" in
start)
echo -n "Starting Tomcat service: "
daemon --user search "$PRGDIR"/startup.sh
iptables -t nat -A PREROUTING -p tcp --dport 80 -j REDIRECT --to-port 8080
;;
stop)
echo -n "Shutting down Tomcat service: "
daemon --user search "$PRGDIR"/shutdown.sh
;;
restart)
$0 stop
$0 start
;;
*)
```

```

echo "Usage: $0 {start|stop|restart}"
exit 1
esac
echo
exit 0
#####

```

```

        user
daemon -user search "$PRGDIR"/startup.sh
iptables          8080  80
iptables -t nat -A PREROUTING -p tcp -dport 80 -j REDIRECT -to-port 8080


```

```

[root@dev ~] chkconfig --add tomcat
[root@dev ~] service tomcat start
[root@dev ~] service tomcat stop

```

## CentOS7 ( )

 ( : ) ( . 2020-02-26)

/usr/lib/systemd/system/tomcat7.service

```

[Unit]

Description=tomcat7
After=network.target syslog.target

[Service]

Type=forking

#tomcat          root,          search
User=root
Group=root

ExecStart=/opt/search/tomcat7/bin/catalina.sh start
ExecStop=/opt/search/tomcat7/bin/catalina.sh stop

Umask=0022
ReStartSec=10
Restart=always

[Install]

```

WantedBy=multi-user.target

```
[root@dev ~] systemctl enable /usr/lib/systemd/system/tomcat7.service
# tomcat7.service tomcat7 가
[root@dev ~] systemctl start tomcat7.service #
[root@dev ~] systemctl start tomcat7.service #
[root@dev ~] systemctl status tomcat7.service #
```

tomccat7.service .

```
[root@dev ~] systemctl daemon-reload
#
[root@dev ~] journalctl -xe
[root@dev ~] journalctl -f #tail
```

## Windows

## Ref

[CentOS7 service\(systemd unit\)](#)

From: <http://rwiki.repia.com/> - . - 2023.12

Permanent link: <http://rwiki.repia.com/doku.php?id=was:tomcat:autostart&rev=1590402544> 

Last update: **2022/03/10 19:52**