

CSS Float Examples

- description : CSS Float Examples
- author : 오션
- email : shlim@repia.com
- lastupdate : 2021-03-15

Source of the article

- CSS Layout - Float Examples

Grid of Boxes / Equal Width Boxes

float속성을 사용하면 콘텐츠 박스들을 쉽게 나란히 배치할 수 있습니다.

예제

```
<!DOCTYPE html>
<html lang="en">

<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Grid of Boxes</title>
    <style>
        * {
            box-sizing: border-box;

            .box {
                float: left;
                width: 33.33%; /* 3개의 박스, 4개 박스는 25%, 2개 박스는 50% */
                padding: 50px;
            }
        }
    </style>

```

```
.clearfix::after {
    content: "";
    clear: both;
    display: table;
}
</style>
</head>

<body>

<h2>Grid of Boxes</h2>
<p>Float boxes side by side:</p>

<div class="clearfix">
    <div class="box" style="background-color:#bbb">
        <p>Some text inside the box.</p>
    </div>
    <div class="box" style="background-color:#ccc">
        <p>Some text inside the box.</p>
    </div>
    <div class="box" style="background-color:#ddd">
        <p>Some text inside the box.</p>
    </div>
</div>

<p>
    Note that we also use the clearfix hack to take care of the layout
    flow, and that we add the box-sizing property to make sure that the box doesn't
    break due to extra padding. Try to remove this
    code to see the effect.
</p>

</body>

</html>
```

3개의 플로팅 박스를 쉽게 나란히 만들 수 있습니다. 하지만 각 박스의 너비를 확대하는 것 (예, 패딩 또는 보더)을 추가할 경우, 박스 배치는 어긋납니다.

"box-sizing" 속성은 해당 박스의 총 너비 (그리고 높이)에 패딩과 보더를 포함하게 하여, 박스 내부에 패딩이 위치하게 하여 박스 배치가 어긋나지 않습니다.

Images Side By Side

박스의 그리드는 이미지를 나란히 보여주는 것에도 사용할 수 있습니다.

예제

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Images Side By Side</title>
  <style>
    * {
      box-sizing: border-box;
    }

    .img-container {
      width: 33.33%;
      padding: 5px;
      float: left;
    }

    .clearfix::after {
      content: "";
      clear: both;
      display: table;
      /* p를 이미지 하단에 배치 */
    }
  </style>
</head>

<body>

  <h2>Images Side by Side</h2>
  <p>Float images side by side</p>

  <div class="clearfix">
    <div class="img-container">
      
    </div>
    <div class="img-container">
      
    </div>
    <div class="img-container">
      
    </div>
  </div>
</body>
</html>
```

```
</div>

<p>
    Note that we also use the clearfix hack to take care of the layout
    flow, and that we add the box-sizing property to make sure that the image
    container doesn't break due to extra padding. Try
    to remove this code to see the effect.
</p>

</body>

</html>
```

Equal Height Boxes

이전의 예제에서, 동일한 너비로 박스들을 나란히 배치하는 방법을 확인하였습니다. 그러나, 동일한 높이로 플로팅 박스들을 만드는 것은 쉽지 않습니다. 하지만, quick fix는 고정 높이를 설정하는 것을 아래 예제에서 살펴보겠습니다.

예제

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Equal Height Boxes</title>
  <style>
    * {
      box-sizing: border-box;
    }

    .box {
      float: left;
      width: 50%;
      padding: 50px;
      height: 300px;
    }

    .clearfix::after {
      content: "";
      clear: both;
    }
  </style>
</head>

<body>
  <div>
    <div class="box">
      <div class="img">
        <img alt="Image placeholder" data-bbox="100 100 250 250" />
      </div>
    </div>
    <div class="box">
      <div class="img">
        <img alt="Image placeholder" data-bbox="300 100 450 250" />
      </div>
    </div>
  </div>
</body>
</html>
```

```

        display: table;
    }
</style>
</head>

<body>

    <h2>Equal Height Boxes</h2>
    <p>Floating boxes with equal heights</p>

    <div class="clearfix">
        <div class="box" style="background-color:#bbb">
            <h2>Box01</h2>
            <p>Some content, some content, some content</p>
        </div>
        <div class="box" style="background-color:#ccc">
            <h2>Box02</h2>
            <p>Some content, some content, some content</p>
            <p>Some content, some content, some content</p>
            <p>Some content, some content, some content</p>
        </div>
    </div>

    <P>
        This example is not very flexible. It is ok to use CSS height if you
        can guarantee that the boxes will always have the same amount of content in
        them, but that's not always the case. If you
        try the example above on a mobile phone (or resize the browser
        window), you will see that the second box's content will be displayed
        outside of the box.
    </P>
    <p>
        Go back to the tutorial and find another solution, if this is not
        what you want.
    </p>
</body>

</html>

```

하지만, 이렇게 하는 것은 매우 유연하지 않습니다. 박스들 내부에 항상 동일한 양의 콘텐츠가 있다는 것을 보장할 수 있는 경우에는 괜찮습니다.

하지만 많은 경우 콘텐츠가 동일하지 않습니다. 상기 예제를 휴대폰에서 시도하면, 두 번째 박스의 콘텐츠가 박스 외부에 표시되는 것을 확인할 수 있습니다.

자동으로 가장 긴 박스만큼 길게 박스를 늘릴 수 있는 CSS3 Flexbox가 이런 경우에 유용합니다.

예제

```

<!DOCTYPE html>
<html lang="en">

```

```
<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Flexible Boxes</title>
  <style>
    .flex-container {
      display: flex;
      flex-wrap: nowrap;
      background-color: dodgerblue;
    }

    .flex-container .box {
      background-color: #f1f1f1;
      width: 50%;
      margin: 10px;
      text-align: center;
      line-height: 75px;
      font-size: 30px;
    }
  </style>
</head>

<body>

  <div class="flex-container">
    <div class="box">
      Box 01 - This is some text to make sure that the content gets
      really tall. This is some text to make sur that the content gets really
      tall.
    </div>
    <div class="box">
      Box 02 - My height will follow Box 01.
    </div>
  </div>

  <p>Try to resize the browser window to see the flexible layout.</p>
  <p>
    <strong>Note:</strong>Flexbox is not supported in Internet Explorer
    10 or earlier versions.
  </p>

</body>

</html>
```

Navigation Menu

하이퍼링크 목록과 float속성을 사용하여 가로 배치 메뉴를 만듭니다.

예제

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Navigation menu with float property</title>
  <style>
    ul {
      list-style-type: none;
      margin: 0;
      padding: 0;
      overflow: hidden;
      background-color: #333;
    }

    li {
      float: left;
    }

    li a {
      display: inline-block;
      color: yellow;
      text-align: center;
      padding: 14px 16px;
      text-decoration: none;
    }

    li a:hover {
      background-color: red;
    }

    .active {
      background-color: blue;
    }
  </style>
</head>

<body>
  <ul>
    <li><a href="#home" class="active">Home</a></li>
    <li><a href="#news">News</a></li>
```

```
<li><a href="#contact">Contact</a></li>
<li><a href="#about">About</a></li>
</ul>
</body>

</html>
```

Web Layout Example

float속성을 사용하여 웹 페이지 전체 레이아웃 작업을 하는 것도 일반적입니다.

예제

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Web page Layout using float property</title>
  <style>
    * {
      box-sizing: border-box;
    }

    .header,
    .footer {
      background-color: grey;
      color: white;
      padding: 15px;
    }

    .column {
      padding: 15px;
      float: left;
    }

    .clearfix::after {
      content: "";
      clear: both;
      display: table;
    }
  </style>
</head>

<body>
  <div class="header">
    <div class="column">
      <h1>Web Page Layout</h1>
    </div>
    <div class="column">
      <h2>Header</h2>
    </div>
  </div>

  <div class="main">
    <div class="column">
      <h3>Left Column</h3>
    </div>
    <div class="column">
      <h3>Right Column</h3>
    </div>
  </div>

  <div class="footer">
    <div class="column">
      <h3>Footer</h3>
    </div>
  </div>
</body>
</html>
```



```
.menu {
    width: 25%;
}

.content {
    width: 75%;
}

.menu ul {
    list-style-type: none;
    margin: 0;
    padding: 0;
}

.menu li {
    padding: 8px;
    margin-bottom: 8px;
    background-color: #33b5e5;
    color: #ffffff;
}

.menu li:hover {
    background-color: #0099cc;
}
</style>
</head>

<body>

<div class="header">
    <h1>Chania</h1>
</div>

<div class="clearfix">
    <div class="column menu">
        <ul>
            <li>The Flight</li>
            <li>The City</li>
            <li>The Island</li>
            <li>The Food</li>
        </ul>
    </div>

    <div class="column content">
        <h1>The City</h1>
        <p>
            Chania is the capital of the Chania region on the island of
            Crete. The city can be divided in two parts, the old town and the modern
            city.
        </p>
    </div>
</div>
```

```
<p>
    You will lern more about web layout an responsive web pages
in a later chapter.
</p>
</div>

</div>
<div class="footer">
    <p>Footer Text</p>
</div>
</body>

</html>
```

[오션](#), [CSS](#), [float](#), [examples](#)

From:
<http://rwiki.repia.com/> - 문제를 잘 정의하는 것은 문제를 절반 해결한 것이다. - 2023.12

Permanent link:
http://rwiki.repia.com/doku.php?id=wiki:css:css_note:css_float_examples&rev=1615858524

Last update: 2022/03/10 19:52

