, Oracle

- description :
- author :
- email : dhan@repia.com
- lastupdate : 2020-03-09

/

1.   (   )

```
sqlplus "/as sysdba"
SQL>
```

2.

```
$> lsnrctl stop
```

3.

```
SQL> shutdown immediate
```

4.

```
SQL> startup
```

5.$> lsnrctl start

DML(   )

VIEW

```
SELECT view_name, text FROM USER_VIEWS WHERE view_name = 'VW_SEARCH_BOARD'
```

DDL

```
SQL> CREATE USER ${USER} IDENTIFIED BY "${PASSWORD}"
     DEFAULT TABLESPACE ${TABLESPACE}
     TEMPORARY TABLESPACE ${TEMP_TABLESPACE}
```

```
       QUOTA UNLIMITED ON ${TABLESPACE};
```

```
SQL> GRANT CREATE SESSION, CREATE TABLE TO ${USER}
```

```
SQL> DROP USER ${USER} cascade;
```

LOCK   (dba user   , system, …)

```
SQL> SELECT * FROM DBA_USERS;
SQL> ALTER USER ${USER} ACCOUNT UNLOCK;
```

,

12   30byte   , 12   256byte
                    JDBC

```
ojdbc14.jar - jdk1.4
ojdbc6.jar - jdk6
ojdbc7.jar - jdk7
ojdbc8.jar - jdk8
```

Ref

- [Oracle]
-           sid, service name
- centos7 oracle 11g r2   1/5 -
- Oracle 11g   Instance
- [Admin][Oracle]
- [ORACLE]DB   1 -Original Utility   exp/imp

- [Oracle]   (Sequence)   (,   ,   ,   )
-                                (alter sequence startwith ???)
- 1.

   ,   , oracle