

HTMLFormElement.reset()

- description : HTMLFormElement.reset()
 - author :
 - email : shlim@repia.com
 - lastupdate : 2022-12-23 Fri

HTMLFormElement.reset()

The `HTMLFormElement.reset()` method restores a form element's default values. This method does the same thing as clicking the form's `<input type="reset">` control.

```
HTMLFormElement.reset()           form  
      form <input type="reset">
```

If a form control (such as a reset button) has a name or id of `reset` it will mask the form's `reset` method. It does not reset other attributes in the input, such as `disabled`.

```
reset      form      reset      id가      , form  reset
가      (?)      )      input      ,      disabled      reset      .
```

Note that if `setAttribute()` is called to set the value of a particular attribute, a subsequent call to `reset()` won't reset the attribute to its default value, but instead will keep the attribute at whatever value the `setAttribute()` call set it to.

setAttribute() , **reset()** **reset()**
setAttribute()

— , () —
— , が , ()

form

가 , form +

Ref Link

[HTMLFormElement.reset\(\)](#)

[HTML DOM Element setAttribute\(\)](#)

[, HTMLFormElement.reset\(\), reset\(\)](#)

From:

<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:

http://rwiki.repia.com/doku.php?id=wiki:html:html_note:htmlformelement.reset&rev=1671795747 

Last update: **2022/12/23 20:42**