

commons-lang3

- description : commons-lang3
- author :
- email : dhan@repia.com
- lastupdate : 2020-03-24

MavanRepository

```
<!-- https://mvnrepository.com/artifact/org.apache.commons/commons-lang3 -->
<dependency>
  <groupId>org.apache.commons</groupId>
  <artifactId>commons-lang3</artifactId>
  <version>3.8</version>
</dependency>
```

[MVN Repository](#)

StringEscapeUtils

 StringEscapeUtils (, 2020-04-06)

StringUtils

StringUtils.abbreviate (,)

4 (3) .

```
String abbreviate = StringUtils.abbreviate("ShowMeTheMoney", 7);
System.out.println(abbreviate);
//      : Show...
```

StringUtils.appendIfMissing (, 가 ,)

가 , 가 .

```
String appendIfMissing = StringUtils.appendIfMissing("ShowMeTheMoney", "-
```

```
From.Choi", "Money");
System.out.println(appendIfMissing);
//           : ShowMeTheMoney

appendIfMissing = StringUtils.appendIfMissing("ShowMeTheMoney", "-
From.Choi", "test");
System.out.println(appendIfMissing);
//           : ShowMeTheMoney-From.Choi
```

```
StringUtil.appendIfMissingIgnoreCase ( , 가 , )
```

StringUtils.appendIfMissing

```
String appendIfMissingIgnoreCase =
StringUtils.appendIfMissingIgnoreCase("ShowMeTheMoney", "-From.Choi",
"money");
System.out.println(appendIfMissingIgnoreCase);
//          : ShowMeTheMoney
```

StringUtils.capitalize ()

```
String capitalize = StringUtils.capitalize("sss");
System.out.println(capitalize);
//      : Sss
```

StringUtils.chomp ()

\n, \r, \r\n

```
String chomp = StringUtils.chomp("sss\n");
System.out.println(chomp);
//          ; sss
```

```
StringUtil.chomp (      ,      )
```

가 .

```
String chomp = StringUtils.chomp("sss#", "#");
System.out.println(chomp);
//          : sss
```

StringUtils.chop ()

.

```
String chop = StringUtils.chop("sss");
System.out.println(chop);
//      : ss
```

StringUtils.center (,)

가 .
 , 가 가 .

```
String center = StringUtils.center("sss", 5);
System.out.println("'" + center + "'");
//      : ' sss '
```

StringUtils.center (, , 가)

가 가 .
 , 가 가 .

```
String center = StringUtils.center("sss", 6, "#");
System.out.println(center);
//      : #sss##
```

StringUtils.compare (,)

.

```
//가, ' '
System.out.println((int) '가');
System.out.println((int) ' ');
//      : 44032
//      : 45208

int compare = StringUtils.compare("가", " ");
System.out.println(compare);
//      : -1176
int compare2 = StringUtils.compare(" ", "가");
System.out.println(compare2);
//      : 1176
```

StringUtils.compareToIgnoreCase (,)

StringUtils.compare

```
int compareIgnoreCase = StringUtils.compareIgnoreCase("A", "a");
System.out.println(compareIgnoreCase);
//           : 0
```

StringUtils.contains (,)

'true' .

```
boolean contains = StringUtils.contains("Hello", "el");
System.out.println(contains);
//           : true
```

StringUtils.containsAny (, 1, 2, ...)

'true' .

```
boolean containsAny = StringUtils.containsAny(" ", "가", " ", " ");
System.out.println(containsAny);
//           : true
```

StringUtils.containsIgnoreCase (,)

StringUtils.contains

```
boolean containsIgnoreCase = StringUtils.containsIgnoreCase("HELLO", "he");
System.out.println(containsIgnoreCase);
//           : true
```

StringUtils.containsNone (,)

'false' .

```
boolean containsNone = StringUtils.containsNone("hello", "h");
System.out.println(containsNone);
//           : false

boolean containsNone = StringUtils.containsNone("hello", "aaah");
System.out.println(containsNone);
//           : false
```

```
StringUtils.containsOnly (      ,      )  
  
                                'true'      .
```

```
boolean containsOnly = StringUtils.containsOnly("hello", "olleh");  
System.out.println(containsOnly);  
//           : true  
  
boolean containsOnly2 = StringUtils.containsOnly("hello", "hell");  
System.out.println(containsOnly2);  
//           : false
```

```
StringUtils.containsWhitespace (      )  
  
                                'true'      .
```

```
boolean containsWhitespace = StringUtils.containsWhitespace("      ");  
System.out.println(containsWhitespace);  
//           : true
```

```
StringUtils.countMatches (      ,      )  
  
                                1 ,      0      .
```

```
int countMatches = StringUtils.countMatches("ABCD", "A");  
System.out.println(countMatches);  
//           : 1  
  
int countMatches2 = StringUtils.countMatches("ABCD", "AB");  
System.out.println(countMatches2);  
//           : 1  
  
int countMatches3 = StringUtils.countMatches("ABCD", "AC");  
System.out.println(countMatches3);  
//           : 0
```

```
StringUtils.defaultIfBlank (      ,      )  
  
                                space(      ),      , null      .
```

```
String defaultIfBlank1 = StringUtils.defaultIfBlank(null, "A");  
System.out.println(defaultIfBlank1);  
//           : A  
  
String defaultIfBlank2 = StringUtils.defaultIfBlank("", "A");
```

```
System.out.println(defaultIfBlank2);
//           : A

String defaultIfBlank3 = StringUtils.defaultIfBlank(" ", "A");
System.out.println(defaultIfBlank3);
//           : A
```

StringUtils.defaultIfEmpty (,)

, null

```
String defaultIfEmpty1 = StringUtils.defaultIfEmpty(null, "B");
System.out.println(defaultIfEmpty1);
//           : B

String defaultIfEmpty2 = StringUtils.defaultIfEmpty("", "B");
System.out.println(defaultIfEmpty2);
//           : B

String defaultIfEmpty3 = StringUtils.defaultIfEmpty(" ", "B");
System.out.println(defaultIfEmpty3);
//           :
```

StringUtils.defaultString (,)

null

```
String defaultString1 = StringUtils.defaultString(null, "C");
System.out.println(defaultString1);
//           : C

String defaultString2 = StringUtils.defaultString("", "C");
System.out.println(defaultString2);
//           :

String defaultString3 = StringUtils.defaultString(" ", "C");
System.out.println(defaultString3);
//           :
```

StringUtils.deleteWhitespace ()

```
String deleteWhitespace = StringUtils.deleteWhitespace(" ");
System.out.println(deleteWhitespace);
```

```
//      :
```

```
StringUtils.difference (      1,      2)
```

```
      2
```

```
String difference = StringUtils.difference("      .", "      .");
System.out.println(difference);
//      :
```

```
StringUtils.endsWith (      ,      )
```

```
      'true',      'false'      .
```

```
boolean endsWith = StringUtils.endsWith("      .", ".");
System.out.println(endsWith);
//      : true

boolean endsWith = StringUtils.endsWith("      ", ".");
System.out.println(endsWith);
//      : false
```

```
StringUtils.endsWithAny (      ,      1,      2, ...)
```

```
StringUtils.endsWith      .
      'true'      .
```

```
boolean endsWithAny = StringUtils.endsWithAny("AAA", "a");
System.out.println(endsWithAny);
//      : false

boolean endsWithAny = StringUtils.endsWithAny("AAA", "a", "A");
System.out.println(endsWithAny);
//      : true
```

```
StringUtils.endsWithIgnoreCase (      ,      )
```

```
StringUtils.endsWith      .
```

```
boolean endsWithIgnoreCase = StringUtils.endsWithIgnoreCase("BBB", "b");
System.out.println(endsWithIgnoreCase);
//      : true
```

```
StringUtils.equals (    1,    2)
```

```
'true'
```

```
boolean equals = StringUtils.equals("abcd", "abcd");
System.out.println(equals);
//          : true

boolean equals = StringUtils.equals("abcd", "Abcd");
System.out.println(equals);
//          : false
```

```
StringUtils.equalsIgnoreCase (      ,      )
```

StringUtils.equals

```
boolean equalsIgnoreCase = StringUtils.equalsIgnoreCase("abcd", "Abcd");
System.out.println(equalsIgnoreCase);
//          : true
```

```
StringUtils.equalsAny (      ,      1,      2, ...)
```

```
StringUtils.equals(
    "true",
    "true"
```

```
boolean equalsAny = StringUtils.equalsAny("abcd", "a", "ab", "abcd");
System.out.println(equalsAny);
//          : true
```

```
StringUtils.equalsAnyIgnoreCase (           ,           1,           2, ...)
```

StringUtils.equalsAny

```
boolean equalsAnyIgnoreCase = StringUtils.equalsAnyIgnoreCase("abc",
    "abcde", "ABC");
System.out.println(equalsAnyIgnoreCase);
//          : true
```

```
StringUtil.firstNonBlank (    1,    2,    3, ...)
```

null, ,

StringUtils v.3.8

```
String firstNonBlank = StringUtils.firstNonBlank(null, "", " ", "first",
"second");
System.out.println(firstNonBlank);
//      : first
```

StringUtils.getCommonPrefix (1, 2, 3, ...)

```
String getCommonPrefix = StringUtils.getCommonPrefix("a", "ab", "abc");
System.out.println(getCommonPrefix);
//      : a
```

StringUtils.getDigits ()

```
String getDigits = StringUtils.getDigits("123    English    456");
System.out.println(getDigits);
//      : 123456
```

StringUtils.indexOf (,)

0 . -1 .

```
int indexOf1 = StringUtils.indexOf("abc", "b");
System.out.println(indexOf1);
//      : 1

int indexOf2 = StringUtils.indexOf("abc", "z");
System.out.println(indexOf2);
//      : -1
```

StringUtils.indexOfIgnoreCase (,)

StringUtils.indexOf

```
int indexOfIgnoreCase = StringUtils.indexOfIgnoreCase("abs", "A");
System.out.println(indexOfIgnoreCase);
```

```
//      : 0
```

```
StringUtils.indexOfAny (      ,      1,      2, ...)
```

StringUtils.indexOf

```
int indexOfAny = StringUtils.indexOfAny("      ", "가", " ", " ", " ");
System.out.println(indexOfAny);
//      : 2
```

```
StringUtils.indexOfAnyBut (      ,      )
```

0

```
int indexOfAnyBut = StringUtils.indexOfAnyBut("      ", " ");
System.out.println(indexOfAnyBut);
//      : 1
```

```
StringUtils.indexOfDifference (      1,      2)
```

0

```
int indexOfDifference = StringUtils.indexOfDifference("      ", " ");
System.out.println(indexOfDifference);
//      : 3
```

Ref

- [StringUtils](#)
- [eleven](#), [stringutils](#), [commonslang](#), [commonslang3](#)

From:
<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:
<http://rwiki.repia.com/doku.php?id=wiki:java:commons-lang&rev=1586766877>

Last update: **2022/03/10 19:52**

