

commons-lang3

- description : commons-lang3
- author :
- email : dhan@repia.com
- lastupdate : 2020-03-24

MavanRepository

```
<!-- https://mvnrepository.com/artifact/org.apache.commons/commons-lang3 -->
<dependency>
  <groupId>org.apache.commons</groupId>
  <artifactId>commons-lang3</artifactId>
  <version>3.8</version>
</dependency>
```

[MVN Repository](#)

StringEscapeUtils

 StringEscapeUtils (, 2020-04-06)

StringUtils

StringUtils.abbreviate (,)

4 (3) .

```
String abbreviate = StringUtils.abbreviate("ShowMeTheMoney", 7);
System.out.println(abbreviate);
//      : Show...
```

StringUtils.appendIfMissing (, 가 ,)

가 , 가 .

```
String appendIfMissing1 = StringUtils.appendIfMissing("ShowMeTheMoney", "-
From.Choi", "Money");
```

```
System.out.println(appendIfMissing1);
//           : ShowMeTheMoney

String appendIfMissing2 = StringUtils.appendIfMissing("ShowMeTheMoney", "-
From.Choi", "test");
System.out.println(appendIfMissing2);
//           : ShowMeTheMoney-From.Choi
```

StringUtils.appendIfMissingIgnoreCase (, 가 ,)

StringUtils.appendIfMissing .

```
String appendIfMissingIgnoreCase =
StringUtils.appendIfMissingIgnoreCase("ShowMeTheMoney", "-From.Choi",
"money");
System.out.println(appendIfMissingIgnoreCase);
//           : ShowMeTheMoney
```

StringUtils.capitalize ()

.

```
String capitalize = StringUtils.capitalize("aaa");
System.out.println(capitalize);
//           : Aaa
```

StringUtils.chomp ()

\n, \r, \r\n .

```
String chomp = StringUtils.chomp("sss\n");
System.out.println(chomp);
//           : sss
```

StringUtils.chomp (,)

가 .

```
String chomp = StringUtils.chomp("sss#", "#");
System.out.println(chomp);
//           : sss
```

StringUtils.chop ()

.

```
String chop = StringUtils.chop("sss");
System.out.println(chop);
//      : ss
```

StringUtils.center (,)

가 .

, 가 가 .

```
String center = StringUtils.center("sss", 5);
System.out.println("'" + center + "'");
//      : ' ss ' '
```

StringUtils.center (, , 가)

가 가 .

, 가 가 .

```
String center = StringUtils.center("sss", 6, "#");
System.out.println(center);
//      : #sss#
```

StringUtils.compare (,)

(-) .

```
//가, ' '
System.out.println((int) '가');
System.out.println((int) ' ');
//      : 44032
//      : 45208

int compare1 = StringUtils.compare("가", " ");
System.out.println(compare1);
//      : -1176
int compare2 = StringUtils.compare(" ", "가");
System.out.println(compare2);
//      : 1176
```

StringUtils.equalsIgnoreCase (,)

StringUtils.compare

```
// 'a', 'A'
System.out.println((int) 'a');
System.out.println((int) 'A');
//      : 97
//      : 65

int compareIgnoreCase = StringUtils.compareIgnoreCase("A", "a");
System.out.println(compareIgnoreCase);
//      : 0
```

StringUtils.contains (,)

'true' .

```
boolean contains = StringUtils.contains("Hello", "el");
System.out.println(contains);
//      : true
```

StringUtils.containsIgnoreCase (,)

StringUtils.contains

```
boolean containsIgnoreCase = StringUtils.containsIgnoreCase("HELLO", "he");
System.out.println(containsIgnoreCase);
//      : true
```

StringUtils.containsAny (, 1, 2, ...)

'true' .

```
boolean containsAny = StringUtils.containsAny(" ", "가", " ", " ");
System.out.println(containsAny);
//      : true
```

StringUtils.containsNone (,)

'false' .

```
boolean containsNone = StringUtils.containsNone("hello", "h");
System.out.println(containsNone);
//      : false
```

```
boolean containsNone = StringUtils.containsNone("hello", "aaah");
System.out.println(containsNone);
//           : false
```

StringUtils.containsOnly (,)

'true' .

```
boolean containsOnly = StringUtils.containsOnly("hello", "olleh");
System.out.println(containsOnly);
//           : true
```

```
boolean containsOnly2 = StringUtils.containsOnly("hello", "hell");
System.out.println(containsOnly2);
//           : false
```

StringUtils.containsWhitespace ()

'true' .

```
boolean containsWhitespace = StringUtils.containsWhitespace(" ");
System.out.println(containsWhitespace);
//           : true
```

StringUtils.countMatches (,)

1 , 0 .

```
int countMatches = StringUtils.countMatches("ABCD", "A");
System.out.println(countMatches);
//           : 1

int countMatches2 = StringUtils.countMatches("ABCD", "AB");
System.out.println(countMatches2);
//           : 1

int countMatches3 = StringUtils.countMatches("ABCD", "AC");
System.out.println(countMatches3);
//           : 0
```

StringUtils.defaultIfBlank (,)

```
space(      ),      , null
```

```
String defaultIfBlank1 = StringUtils.defaultIfBlank(null, "A");
System.out.println(defaultIfBlank1);
//          : A

String defaultIfBlank2 = StringUtils.defaultIfBlank("", "A");
System.out.println(defaultIfBlank2);
//          : A

String defaultIfBlank3 = StringUtils.defaultIfBlank("  ", "A");
System.out.println(defaultIfBlank3);
//          : A
```

```
StringUtils.defaultIfEmpty (      ,      )
```

, null

```
String defaultIfEmpty1 = StringUtils.defaultIfEmpty(null, "B");
System.out.println(defaultIfEmpty1);
//          : B

String defaultIfEmpty2 = StringUtils.defaultIfEmpty("", "B");
System.out.println(defaultIfEmpty2);
//          : B

String defaultIfEmpty3 = StringUtils.defaultIfEmpty("  ", "B");
System.out.println(defaultIfEmpty3);
//          :
```

```
StringUtils.defaultString (    ,    )
```

null

```
String defaultString1 = StringUtils.defaultString(null, "C");
System.out.println(defaultString1);
//          : C

String defaultString2 = StringUtils.defaultString("", "C");
System.out.println(defaultString2);
//          :

String defaultString3 = StringUtils.defaultString("  ", "C");
System.out.println(defaultString3);
//          :
```

StringUtils.deleteWhitespace ()

```
String deleteWhitespace = StringUtils.deleteWhitespace("            ");
System.out.println(deleteWhitespace);
//            :
```

StringUtils.difference (1, 2)

2

```
String difference = StringUtils.difference("            .", "            .");
System.out.println(difference);
//            :
```

StringUtils.endsWith (,)

'true', 'false' .

```
boolean endsWith = StringUtils.endsWith("            .", ".");
System.out.println(endsWith);
//            : true

boolean endsWith = StringUtils.endsWith("            ", ".");
System.out.println(endsWith);
//            : false
```

StringUtils.endsWithAny (, 1, 2, ...)

StringUtils.endsWith

'true' .

```
boolean endsWithAny = StringUtils.endsWithAny("AAA", "a");
System.out.println(endsWithAny);
//            : false

boolean endsWithAny = StringUtils.endsWithAny("AAA", "a", "A");
System.out.println(endsWithAny);
//            : true
```

StringUtils.endsWithIgnoreCase (,)

StringUtils.endsWith

.

```
boolean endsWithIgnoreCase = StringUtils.endsWithIgnoreCase("BBB", "b");
System.out.println(endsWithIgnoreCase);
//           : true
```

StringUtils.equals (1, 2)

'true' .

```
boolean equals = StringUtils.equals("abcd", "abcd");
System.out.println(equals);
//           : true
```

```
boolean equals = StringUtils.equals("abcd", "Abcd");
System.out.println(equals);
//           : false
```

StringUtils.equalsIgnoreCase (,)

StringUtils.equals .

```
boolean equalsIgnoreCase = StringUtils.equalsIgnoreCase("abcd", "Abcd");
System.out.println(equalsIgnoreCase);
//           : true
```

StringUtils.equalsAny (, 1, 2, ...)

StringUtils.equals .
'true' .

```
boolean equalsAny = StringUtils.equalsAny("abcd", "a", "ab", "abcd");
System.out.println(equalsAny);
//           : true
```

StringUtils.equalsAnyIgnoreCase (, 1, 2, ...)

StringUtils.equalsAny .

```
boolean equalsAnyIgnoreCase = StringUtils.equalsAnyIgnoreCase("abc",
"abcde", "ABC");
System.out.println(equalsAnyIgnoreCase);
//           : true
```

StringUtils.firstNonBlank (1, 2, 3, ...)

null, , .

StringUtils v.3.8 .

```
String firstNonBlank = StringUtils.firstNonBlank(null, "", " ", "first",
"second");
System.out.println(firstNonBlank);
//      : first
```

StringUtils.getCommonPrefix (1, 2, 3, ...)

.

```
String getCommonPrefix = StringUtils.getCommonPrefix("a", "ab", "abc");
System.out.println(getCommonPrefix);
//      : a
```

StringUtils.getDigits ()

.

```
String getDigits = StringUtils.getDigits("123 English 456");
System.out.println(getDigits);
//      : 123456
```

StringUtils.indexOf (,)

0 . -1 .

```
int index0f1 = StringUtils.indexOf("abc", "b");
System.out.println(index0f1);
//      : 1

int index0f2 = StringUtils.indexOf("abc", "z");
System.out.println(index0f2);
//      : -1
```

StringUtils.indexOfIgnoreCase (,)

StringUtils.indexOf .

```
int indexOfIgnoreCase = StringUtils.indexOfIgnoreCase("abs", "A");
System.out.println(indexOfIgnoreCase);
//           : 0
```

StringUtils.indexOfAny (, 1, 2, ...)

StringUtils.indexOf .

```
int indexOfAny = StringUtils.indexOfAny(" ", "가", " ", " ", " ");
System.out.println(indexOfAny);
//           : 2
```

StringUtils.indexOfAnyBut (,)

0 .

```
int indexOfAnyBut = StringUtils.indexOfAnyBut(" ", " ");
System.out.println(indexOfAnyBut);
//           : 1
```

StringUtils.indexDifference (1, 2)

0 .

```
int indexDifference = StringUtils.indexDifference(" ", " ");
System.out.println(indexDifference);
//           : 3
```

Ref

- [StringUtils](#)
[, eleven](#), [stringutils](#), [commonslang](#), [commonslang3](#)

From:

<http://rwiki.repia.com/> -
2023.12

Permanent link:

<http://rwiki.repia.com/doku.php?id=wiki:java:commons-lang&rev=1586767635>

Last update: **2022/03/10 19:52**

