

Java

- description :
- author :
- email : dhan@repia.com
- lastupdate : 2020-03-09

Java

() Oracle / Code Conventions for Java™ Programming Language / 1999-4-20
 ()

```

1.
    extends
2.
    가 super();
    ,
    가
3.
    (@Override)
    ( , , ) 가
    ,
    (public, protected, default, private)
    @Override
    super. ()
4. final
    final class: String final
    final method():
5. (Polymorphism)
6. instanceof
    : if(A instanceof B )
7. (abstract)
    (new) 가
    가
    1. ( )
  
```

```

2.
[public | protected] abstract
        (
        , ...);
        @Override
        .

```

public	, ,	
protected	, ,	가
default	, ,	
private	, ,	

()

- [Batch\(\)_ _DB](#)
- [JDBC](#)
- [Math](#)
-
- [Jenkins\(\)](#)

- [get, post 가](#)
- [ibatis to mybatis](#)
- [jackson](#)
- [jsoup](#)
- [List](#)
- [Regular Expression](#)
-
-
-

[/ How to check whether an array contains a particular value in java](#)

(Javascript)

base URL .

```

function absolute(base, relative) {
    var stack = base.split("/"),
        parts = relative.split("/");
    stack.pop(); // remove current file name (or empty string)
                // (omit if "base" is the current folder without trailing
slash)
    for (var i=0; i<parts.length; i++) {
        if (parts[i] == ".")
            continue;

```

```
        if (parts[i] == "..")
            stack.pop();
        else
            stack.push(parts[i]);
    }
    return stack.join("/");
}
```

- [XSS injection prevention](#)

Apache-commons

- commons-lang
 - [StringUtils](#)
- commons-io
 - [FileUtils](#)
- commons-codec
 - [Base64](#)

Cast

[Convert double to float in Java](#)

```
double d = getInfoValueNumeric();
float f = (float)d;
```

// Also notice that the primitive types can NOT store an infinite set of numbers:

// float range: from 1.40129846432481707e-45 to 3.40282346638528860e+38
// double range: from 1.7e-308 to 1.7e+308

Date

-
-
- [Date java](#) , , ,

enum

Naming (Week.java, Role.java, ...) // Camel case
(MONDAY, ROOT, ...) // Snake case

Calendar.class ~ ...

TableStatus.java

```
// public enum <-
//
public enum TableStatus
{
    Y("1", true)
    , N("0", false);

    private String table1Value;
    private boolean table2Value;

    TableStatus(String table1Value, boolean table2Value)
    {
        this.table1Value = table1Value;
        this.table2Value = table2Value;
    }

    public String getTable1Value()
    {
        return table1Value;
    }

    public boolean isTable2Value() { return table2Value; }
}
```

- values()
 -
- ordinal()
 -
- valueOf()
 - String String 가 IllegalArgumentException
 - String 가 IllegalArgumentException

Java Enum
enum

Reflection

- [Call Methods at Runtime Using Java Reflection](#)

Servlet, Request, Context

- [Servlet, Request, Context](#)

String

- [replaceAll, replace](#)

Thread

-

- `try{} catch(){} finally{}`

- [e.toString\(\), e.getMessage\(\), e.printStackTrace\(\)](#)
- [Spring Guide - Exception](#)

Ref

- [concurrency](#)
 - [fcntl](#)
- , [java](#), [doc2vec](#)

From:
<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:
<http://rwiki.repia.com/doku.php?id=wiki:java&rev=1599182636>



Last update: **2022/03/10 19:52**