

# Javascript HTML DOM classList Property

- description : Javascript HTML DOM classList Property
- author :
- email : shlim@repia.com
- lastupdate : 2021-06-08

## The source of the article

[Javascript HTML DOM classList Property](#)

### Example

<div> "mystyle" 가 .

```
<head>
  <style>
    .mystyle {
      width: 300px;
      height: 50px;
      background-color: coral;
      color: white;
      font-size: 25px;
    }
  </style>
</head>
<body>
  <p>Click the button to add the "mystyle" class to DIV.</p>

  <button onclick="myFunction()">Try it</button>

  <p><strong>Note:</strong> The classList property is not supported in
  Internet Explorer 9 and earlier versions.</p>

  <div id="myDIV">I am a DIV element</div>

  <script>
    function myFunction() {
      document.getElementById('myDIV').classList.add('mystyle');
      /*      mystyle      가 myDIV      가      */
    }
  </script>
```

</body>

## Definition and Usage

`classList` is a property of `DOMTokenList` objects that returns a `DOMTokenList` object representing the CSS class names of the element that the `DOMTokenList` object represents. The `DOMTokenList` object has methods to add, remove, and toggle CSS class names of the element.

`classList` is a property of `Element` objects that returns a `DOMTokenList` object representing the CSS class names of the element that the `Element` object represents. The `DOMTokenList` object has methods to add, remove, and toggle CSS class names of the element.

`classList` is not supported in Internet Explorer 9 and earlier versions. Use `className` property instead.

## Syntax

`element.classList`

## Properties

Property	Description
<code>length</code>	The number of class names in the <code>classList</code> object.

## Methods

Method	Description
<code>add(class1, class2,...)</code>	Adds the class names <code>class1</code> , <code>class2</code> , and so on to the <code>classList</code> object.
<code>contains(class)</code>	Checks if the <code>classList</code> object contains the class name <code>class</code> . true - if the class name is in the <code>classList</code> object. false - if the class name is not in the <code>classList</code> object.
<code>item(index)</code>	Returns the class name at the index <code>index</code> . If <code>index</code> is 0, it returns the first class name. If <code>index</code> is <code>length - 1</code> , it returns the last class name. If <code>index</code> is not a valid index, it returns <code>null</code> .
<code>remove(class1, class2,...)</code>	Removes the class names <code>class1</code> , <code>class2</code> , and so on from the <code>classList</code> object. <b>Note:</b> If the class name is not in the <code>classList</code> object, it does nothing.

Method	Description
toggle(class, true or false)	.
	false .
	가 , 가 , true .
	가 가 .
	: element.classList.toggle("classToRemove", false);
	가 : element.classList.toggle("classToAdd", true);
	<b>Note:</b> Internet Explorer Opera 12

## Technical Details

Return Value	DOMTokenList
--------------	--------------

## More Examples

### Example

<div> 가 .

```

<head>
  <style>
    .mystyle {
      width: 500px;
      height: 50px;
      padding: 15px;
      border: 5px solid dodgerblue;
    }

    .anotherClass {
      background-color: coral;
      color: white;
    }

    .thirdClass {
      text-transform: uppercase;
      text-align: center;
      font-size: 25px;
    }
  </style>
</head>
<body>
  <p>Click the button to add multiple classes to DIV.</p>

  <button onclick="myFunction()">Try it</button>

```

```
<p><strong>Note:</strong> The classList property is not supported
in Internet Explorer 9 and earlier versions.</p>

<div id="myDIV">I am a DIV element.</div>

<script>
  function myFunction() {
    document.getElementById('myDIV').classList.add('mystyle',
'anotherClass', 'thirdClass');
  }
  /*          <div id="myDIV">I am a DIV element.</div>
  <div id="myDIV" class="mystyle anotherClass thirdClass">
가      */
</script>
</body>
```

## Example

<div>

```
<head>
  <style>
    .mystyle {
      width: 500px;
      height: 50px;
      background-color: forestgreen;
      color: white;
      font-size: 25px;
    }
  </style>
</head>
<body>
  <p>Click the button to remove the "mystyle" class from DIV.</p>

  <button onclick="myFunction()">Try it!</button>

  <p><strong>Note:</strong> The classList property is not supported
in Internet Explorer 9 and earlier versions.</p>

  <div id="myDIV" class="mystyle">I am a DIV element.</div>

  <script>
    function myFunction() {
      document.getElementById('myDIV').classList.remove('mystyle');
    } /*          #myDIV          .mystyle          */
  </script>
</body>
```

## Example

<div>

```
<head>
  <style>
    .mystyle {
      width: 500px;
      height: 50px;
      padding: 15px;
      border: 5px solid dodgerblue;
    }

    .anotherClass {
      background-color: coral;
      color: white;
    }

    .thirdClass {
      text-transform: uppercase;
      text-align: center;
      font-size: 25px;
    }
  </style>
</head>
<body>
  <p>Click the button to remove multiple classes to DIV.</p>

  <button onclick="myFunction()">Try it</button>

  <p><strong>Note:</strong> The classList property is not supported
  in Internet Explorer 9 and earlier versions.</p>

  <div id="myDIV" class="mystyle anotherClass thirdClass">I am a DIV
  element.</div>

  <script>
    function myFunction() {
      document.getElementById('myDIV').classList.remove('mystyle',
      'anotherClass', 'thirdClass');
    }
  /*           <div id="myDIV" class="mystyle anotherClass thirdClass">

    <div id="myDIV">I am a DIV element.</div>           CSS           */
</script>
</body>
```

## Example

<div>

```
<head>
  <style>
    .mystyle {
      width: 300px;
      height: 50px;
      background-color: coral;
      color: white;
      font-size: 25px;
    }

    .newClassName {
      width: 400px;
      height: 100px;
      background-color: lightblue;
      text-align: center;
      font-size: 25px;
      color: navy;
      margin-bottom: 10px;
    }
  </style>
</head>
<body>
  <p>Click the button to toggle between two classes.</p>

  <button onclick="myFunction()">Try it</button>

  <p><strong>Note:</strong> The classList property is not supported
  in Internet Explorer 9 and earlier versions.</p>

  <div id="myDIV" class="mystyle">I am a DIV element.</div>

  <script>
    function myFunction() {
      document.getElementById('myDIV').classList.toggle('newClassName');
    }
    /*          <div id="myDIV" class="mystyle">
    <div id="myDIV" class="mystyle newClassName">          */
  </script>
</body>
```

## Example

<div>

가 .

```
<head>
  <style>
```

```

    .mystyle {
      width: 500px;
      height: 50px;
    }

    .anotherClass {
      background-color: lightblue;
    }

    .thirdClass {
      text-align: center;
      font-size: 25px;
      color: black;
      margin-bottom: 10px;
    }
  </style>
</head>
<body>
  <p>Click the button to display the class names of the div element.</p>

  <div id="myDIV" class="mystyle anotherClass thirdClass">
  I am a DIV element with multiple classes.</div>

  <button onclick="myFunction()">Try it</button>

  <p><strong>Note:</strong> The classList property is not supported
  in Internet Explorer 9 and earlier versions.</p>

  <p id="demo"></p>

  <script>
    function myFunction() {
      var x = document.getElementById('myDIV').classList;
      document.getElementById('demo').innerHTML = x;
    }
    /* mystyle anotherClass thirdClass */
    /* id="myDIV"가 div 가 */
  </script>
</body>

```

## Example

<div> 가 가 .

```

<head>
  <style>
    .mystyle {
      width: 500px;
      height: 50px;
    }

```

```
.anotherClass {
  background-color: lightblue;
}

.thirdClass {
  text-align: center;
  font-size: 25px;
  color: black;
  margin-bottom: 10px;
}
</style>
</head>
<body>
  <p>Click the button to display the number of class names the div element
  has.</p>

  <div id="myDIV" class="mystyle anotherClass thirdClass">I am a DIV
  element with three classes.</div>

  <button onclick="myFunction()">Try it</button>

  <p><strong>Note:</strong> The classList property is not supported in
  Internet Explorer 9 and earlier versions.</p>

  <p id="demo"></p>

  <script>
    function myFunction() {
      var x = document.getElementById('myDIV').classList.length;
      document.getElementById('demo').innerHTML = x;
    }
    /*          id="myDIV" 가          div          . */
  </script>
</body>
```

## Example

<div> (index 0) 가 .

## Example

가 "mystyle" 가 .

,, Javascript, HTML, DOM, classList, Property

From:

<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:

[http://rwiki.repia.com/doku.php?id=wiki:javascript:javascript\\_note:classlist\\_property&rev=1623128765](http://rwiki.repia.com/doku.php?id=wiki:javascript:javascript_note:classlist_property&rev=1623128765) 

Last update: **2022/03/10 19:52**