

Javascript Regular Expressions

- description : Javascript Regular Expressions
- author :
- email : shlim@repia.com
- lastupdate : 2021-04-22

The source of this article

[Javascript Regular Expressions](#)

(Regular Expression,)

replace

What is a Regular Expression?

(Regular Expression,)

(text search)

(text replace)

Syntax

```
/pattern/modifiers;
```

Example

```
var patt = /w3schools/i;
```

:

/w3schools/i ()

w3schools () .

i () (modifier) .

Using String Methods

JavaScript , search() replace() 가 .

search() , .

replace() .

Using String search() With a String

search() .

Example

["W3schools" string .

```
<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>Search a string for "W3schools", and display the position of the
match.</p>
  <p id="demo"></p>  <!-- 6 -->
  <script>
    let str = "Visit W3Schools!";
    let n = str.search("W3Schools"); /* W3Schools가 ? */
    document.getElementById("demo").innerHTML = n;
  </script>
</body>
</html>
```

Using String search() With a Regular Expression

Example

"w3schools" .

```
<!DOCTYPE html>
```

```

<html>
<body>
  <h2>JavaScript Regular Expressions</h2>
  <p>Search a string for "w3schools", and display the position of the
match:</p>
  <p id="demo"></p>  <!-- 6 -->
  <script>
    let str = "Visit W3Schools!";
    let n = str.search(/w3Schools/i); /*
? */
    document.getElementById("demo").innerHTML = n;
  </script>
</body>
</html>

```

Using String replace() With a String

replace()

```

<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>Replace "Microsoft" with "W3Schools" in the paragraph below:</p>
  <button onclick="myFunction()">Try it</button>
  <p id="demo">Please visit Microsoft!</p>  <!-- Please visit W3Schools! -
->
  <script>
    function myFunction() {
      let str = document.getElementById("demo").innerHTML;
      let txt = str.replace("Microsoft", "W3Schools");
      document.getElementById("demo").innerHTML = txt;
    }
  </script>
</body>
</html>

```

Use String replace() With a Regular Expression

W3Schools (a case insensitive regular expression) Microsoft


```

<!DOCTYPE html>
<html>
<body>

```

```
<h2>JavaScript Regular Expressions</h2>
<p>Replace "Microsoft" with "W3Schools" in the paragraph below:</p>
<button onclick="myFunction()">Try it</button>
<p id="demo">Please visit Microsoft and Microsoft!</p>
<script>
  function myFunction() {
    let str = document.getElementById("demo").innerHTML;
    let txt = str.replace(/microsoft/i, "W3Schools");
    document.getElementById("demo").innerHTML = txt;
  }
</script>
</body>
</html>
```

Did You Notice?



Regular Expression Modifiers

(Modifiers)

Modifier	Description
i	
g	()
m	.

Example of i modifier

```
<script>
  function myFunction() {
    let str = "Visit W3Schools";
    let patt1 = /w3schools/i; /* w3schools patt1 */
    let result = str.match(patt1); /* str patt1(result) */
    document.getElementById("demo").innerHTML = result; /* result */
  }
</script>
```

Example of g modifier

```
<script>
  function myFunction() {
    let str = "Is this all there is?";
    let patt1 = /is/g; /*
    let result = str.match(patt1);
    document.getElementById("demo").innerHTML = result;
  }
```

Example of m modifier

```
<script>
  function myFunction() {
    let str = "\nIs th\nis it?";
    let patt1 = /^is/m;
    let result = str.match(patt1);
    document.getElementById("demo").innerHTML = result; /* is */
  }
</script>
```

Regular Expression Patterns

:

Expression	Description
[abc]	.
[0-9]	.
(x y)	alternatives .

Example of [abc] pattern

```
<script>
  function myFunction() {
    let str = "Is this all there is?";
    let patt1 = /[h]/g;
    let result = str.match(patt1);
    document.getElementById("demo").innerHTML = result; /* h,h */
  }
</script>
```

Example of [0-9] pattern

```
<script>
```

```
function myFunction() {
    let str = "123456789";
    let patt1 = /[1-4]/g; /* str 1~4 patt1 */
    var result = str.match(patt1); /* patt1 str result */
    document.getElementById("demo").innerHTML = result; /* 1,2,3,4 */
}
</script>
```

Example of (x|y) pattern

```
<script>
function myFunction() {
    let str = "re, green, red, green, gren, gr, blue, yellow";
    let patt1 = /(red|green)/g;
    let result = str.match(patt1);
    document.getElementById("demo").innerHTML = result; /* green, red, green */
}
</script>
```

Metacharacters are characters with a special meaning:

Metacharacter() :

Metacharacter	Description
\d	(digit) . digit: 0 9 10
\s	(whitespace character)
\b	\ bWORD WORD \ b
\uxxx	16 xxxx .

Example of Metachatacters (\d)

```
<script>
function myFunction() {
    let str = "Give 100%!";
    let patt1 = /\d/g; /* \d patt1 */
    let result = str.match(patt1); /* str patt1 result */
    document.getElementById("demo").innerHTML = result; /* 1,0,0 */
}
</script>
```

```
</script>
```

Example of Metacharacters (\s)

```
<script>
function myFunction() {
  let str = "Is this all there is?";
  let patt1 = /\s/g; /* (whitespace) */
  let result = str.match(patt1);
  document.getElementById("demo").innerHTML = result; /* [" ", " ", " ",
" "] */
  console.log(result, result.length);
}
</script>
```

Exmample of Metacharacters (\b)

```
<script>
let str = "HELLO, LOOK AT YOU!";
let patt1 = /\bLO/g; /* LO */
let result = str.search(patt1);
document.getElementById("demo").innerHTML = result; /* Found in
position: 7 */
console.log(result, result.length); /* 7 undefined */
</script>
```

Exmample of Metacharacters (\b)

```
<script>
let str = "HELLO, LOOK AT YOU";
let patt1 = /LO\b/; /* LO가 가 */
let result = str.search(patt1);
document.getElementById("demo").innerHTML = result; /* Found in
position: 3 */
</script>
```

Example of Metacharacters (\uxxxx)

```
<script>
function myFunction() {
  let str = "Visit W3Schools. Hello World!";
  let patt1 = /\u0057/g;
  let result = str.match(patt1);
  document.getElementById("demo").innerHTML = result; /* W,W */
}
</script>
```

```
</script>
```

Quantifiers define quantities

Quantifier	Description
n+	n .
n*	n 0 .
n?	n 0 1 .

Example of Quantifiers (n+)

```
<script>
function myFunction() {
  let str = "Hellooo World! Hello W3Schools!";
  let patt1 = /o+/g; /* o가 */
  let result = str.match(patt1);
  document.getElementById("demo").innerHTML = result; /* ooo,o,o,oo */
}
</script>
```

Example of Quantifiers (n*)

```
<script>
function myFunction() {
  let str = "Hellooo World! Hello W3Schools!";
  let patt1 = /lo*/g;
  let result = str.match(patt1);
  document.getElementById("demo").innerHTML = result; /* l,l,loo,l,l,lo,l
*/
}
</script>
```

Example of Quantifiers (n?)

```
<script>
function myFunction() {
  let str = "1, 100 or 1000?";
  let patt1 = /10?/g;
  let result = str.match(patt1);
  document.getElementById("demo").innerHTML = result; /* 1,10,10 */
}
</script>
```


Using the RegExp Object

JavaScript

RegExp

가

Using test()

```

""test()
RegExp( )
, true false
"e"
====Example==== <code javascript> var patt = /e/; patt.test("The best things
in life are free!"); </code>
"e"가 true
가

```

```

<code javascript> /e/.test("The best things in life are free!"); </code>
<code javascript> <!DOCTYPE html> <html> <body> <h2>JavaScript Regular
Expressions</h2> <p>Search for an "e" in the next paragraph:</p> <p
id="p01">The best things in life are free!</p> <p id="demo"></p> <script>
text = document.getElementById("p01").innerHTML;
document.getElementById("demo").innerHTML = /e/.test(text); </script> </body>
</html> </code>
====Using exec()==== exec()"
RegExp
,
, (null)
"e"

```

Example

Complete RegExp Reference

[Complete JavaScript RegExp Reference](#)

RegExp

가

, [Javascript](#), [Regular](#), [Expressions](#)

Last update: 2022/03/10 19:52
wiki:javascript:javascript_note:js_regexp http://rwiki.repia.com/doku.php?id=wiki:javascript:javascript_note:js_regexp&rev=1619080784

From:
<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:
http://rwiki.repia.com/doku.php?id=wiki:javascript:javascript_note:js_regexp&rev=1619080784

Last update: **2022/03/10 19:52**

