

Javascript HTML DOM Document querySelectorAll() Method

- description : Javascript HTML DOM Document querySelectorAll() Method
- author :
- email : shlim@repia.com
- lastupdate : 2021-05-26

The source of the article

[HTML DOM Document querySelectorAll\(\) Method](#)

Example

class="example" 가 가 .

```
<body>

<h2 class="example">A heading with class="example"</h2> <!-- red
-->
<p class="example">A paragraph with class="example"</p> <!-- red
-->

<p>
  Click the button to add a background color to all elements with
  class="example".
</p>

<button onclick="myFunction()">Try it</button>

<p><strong>Note:</strong> The querySelectorAll() method is not supported
in Internet Explorer 8 and earlier versions.</p>

<script>
  function myFunction() {
    var x, i;
    x = document.querySelectorAll(".example");
    for (i = 0; i < x.length; i++) {
      x[i].style.backgroundColor = "red";
    }
  }
}
```

```
</script>

</body>
```

Definition and Usage

`querySelectorAll()` (static) `NodeList` .

`NodeList` . 0 .

Tip: `NodeList` .

CSS , [CSS Selectors Tutorial](#)
[CSS Selectors Reference](#) .

Browser Support

Note: Internet Explorer 8 CSS2 . IE9 CSS3 .

Syntax

```
document.querySelector(CSS selectors)
```

Parameter Values

Parameter	Type	Description
CSS selectors	String	CSS ID, HTML . Tip: CSS CSS Selectors Reference .

Technical Details

DOM Version	Selectors Level 1 Document Object			
Return Value	CSS NodeList (static) 가	DOM SYNTAX_ERR 가	NodeList .	.

More Examples

Example

<p>가, <p> (index 0) .

```
<body>

  <p>This is a p element.</p> <!-- red -->

  <p>This is also a p element.</p>

  <p>
    Click the button to add a background color
    to the first p element (index 0) in the document.
  </p>

  <button onclick="myFunction()">Try it</button>

  <p><strong>Note:</strong> The querySelectorAll() method is not supported
  in Internet 8 and eralier versions.</p>

  <script>
    function myFunction() {
      var x = document.querySelectorAll("p");
      // Get all <p> elements in the document.
      x[0].style.backgroundColor = "red";
      // Set the background color of the first <p> element
    }
  </script>

</body>
```

Example

class="example" <p>가, <p> .

```
<body>
```

```
<h2 class="example">A heading with class="example"</h2>
<p class="example">A paragraph with class="example"</p>
<p class="example">Another paragraph with class="example".</p> <!-- yellow
-->

<p>
  Click the button to add a background color to the first p element (index
0) in the document with class="example".
</p>

<button onclick="myFunction()">Try it</button>

<p><strong>Note:</strong> The querySelctorAll() method is not supported in
Internet Explorer 8 and earlier versions.</p>

<script>
  function myFunction() {
    var x = document.querySelectorAll("p.example");
    // Get all <p> elements in the document with class="example"
    x[1].style.backgroundColor = "yellow";
    // Set the background color of the second <p> element with
class="example" (index 1)
  }
</script>

</body>
```

Example

class="example" 가 (NodeList length).

```
<body>

  <div class="example">
    A div element with class="example"
  </div>

  <div class="example">
    Another div element with class="example"
  </div>

  <p class="example">A p element with class="example"</p>

  <p>
    Click the button to find out how manu elements with class "example"
there are in this document.
```

```

</p>

<button onclick="myFunction()">Try it</button>

<p><strong>Note:</strong> The querySelectorAll() method is not supported
in Internet Explorer 8 and earlier versions.</p>

<p id="demo"></p>

<script>
  function myFunction() {
    var x = document.querySelectorAll(".example");
    document.getElementById("demo").innerHTML = x.length; // 3
    console.log(x); // NodeList(3) [div.example, div.example, p.example]
  }
</script>

</body>

```

Example

class="example"

```

<head>
  <style>
    .example {
      border: 1px solid #000;
      margin: 5px;
    }
  </style>
</head>

<body>

  <div class="example">
    A div with class="example"
    <!-- red -->
  </div>

  <div class="example">
    Another div with class="example"
    <!-- red -->
  </div>

  <p class="example">This is a p element with class="example"</p> <!-- red -->

  <p>This is a <span class="example">span</span> element with

```

```
class="example" inside another p element.</p> <!-- span red -->

<p>Click the button to change the background color of all elements with
class="example".</p>

<button class="example" onclick="myFunction()">Try it</button> <!-- red
-->

<p><strong>Note:</strong> The querySelectorAll() method is not supported
in Internet Explorer 8 and earlier versions.</p>

<script>
function myFunction() {
var x = document.querySelectorAll(".example");
var i;
for (i = 0; i < x.length; i++) {
x[i].style.backgroundColor = "red";
}
console.log(x);
/* NodeList(5)[div.example, div.example, p.example, span.example,
button.example] */
}
</script>

</body>
```

Example

<p> .

```
<head>
<style>
.example {
border: 1px solid #000;
margin: 5px;
}
</style>
</head>

<body>

<h1>A h1 element</h1>

<div>A div element</div>

<p>A p element</p> <!-- red -->
```

```

<p>Another p element</p> <!-- red      -->

<div class="example">
  <p>A p element inside a div element.</p> <!-- red      -->
</div>

<p>
  Click the button to change the background color of all p elements in the
  document.
  <!-- red      -->
</p>

<button onclick="myFunction()">Try it</button>

<p><strong>Note:</strong> The querySelectorAll() method is not supported
in Internet Explorer 8 and earlier versions.</p> <!-- red      -->

<script>
  function myFunction() {
    var x = document.querySelectorAll("p");
    var i;
    for (i = 0; i < x.length; i++) {
      x[i].style.backgroundColor = "red";
    }
    console.log(x); /* NodeList(5) [p, p, p, p, p] */
  }
  /* console.log(x); */
  /* Uncaught ReferenceError: x is not defined */
</script>

</body>

```

Example

"target" 가 <a> .

```

<head>
  <style>
    a[target] {
      background-color: yellowgreen;
    }
  </style>
</head>

<body>
  <p>
    The CSS selector a[target] makes sure that all links with a target

```

attribute gets a yellow background:

```
</p>

<a href="https://www.w3schools.com">w3schools.com</a>
<a href="http://www.disney.com" target="_blank">disney.com</a> <!-- 10px
solid red border -->
<a href="http://www.wikipedia.org" target="_top">wikipedia.org</a> <!--
10px solid red border -->

<p>
    Click the button to add a red border to all links in the document with a
    target attribute.
</p>

<button onclick="myFunction()">Try it</button>

<p><strong>Note:</strong> The querySelectorAll() method is not supported
in Internet Explorer 8 and earlier versions.</p>

<script>
    function myFunction() {
        var x = document.querySelectorAll("a[target]");
        var i;
        for (i = 0; i < x.length; i++) {
            x[i].style.border = "10px solid red";
        }
    }
</script>

</body>
```

., Javascript, HTML, DOM, Document, querySelectorAll(), Method

From:
<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:
http://rwiki.repia.com/doku.php?id=wiki:javascript:javascript_note:querySelectorall&rev=1622003691

Last update: 2022/03/10 19:52

