

jQuery addClass() Method

- description : jQuery addClass() Method
- author :
- email : shlim@repia.com
- lastupdate : 2021-06-09

The source of this article

[jQuery addClass\(\) Method](#)

Example

<p> 가 .

```

<head>
  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></scr
ipt>
  <style>
    .intro {
      font-size: 150%;
      color: red;
    }
  </style>
</head>
<body>
  <h1>This is a heading.</h1>

  <p>This is a paragraph.</p>
  <!--           p           가   가
  <p class="intro">This is a paragraph.</p>           ,           .-->
  <p>This is another paragraph.</p>
  <button>Add a class name to the first p element</button>

  <script>
    $(document).ready(function () {
      $('button').click(function () {
        $('p:first').addClass('intro');
      });
    });
  </script>

```

</body>

Definition and Usage

`addClass()` is a jQuery method that adds the specified class(es) to the selected elements.

Tip: Use `removeClass()` to remove class(es) from the selected elements.

Syntax

```
$(selector).addClass(classname, function(index, currentclass))
```

Parameter	Description
classname	The class(es) to be added to the selected elements.
function(index, currentclass)	A function to be executed for each element in the set. index - The index of the current element in the set. currentclass - The current class of the element.

More Examples

Example

가 .

```
<head>
  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></scr
ipt>
  <style>
    .intro {
      font-size: 30px;
      color: blue;
    }
    .note {
      background-color: yellow;
    }
  </style>
</head>
<body>
  <h1>This is a heading</h1>
```

```

<p>This is a paragraph</p>
<!--      <p class="intro note">This is a paragraph</p>      p
intro class  note class가      . -->
<p>This is another paragraph</p>

<button>Add two class name to the first p element</button>

<script>
$(document).ready(function () {
    $('button').click(function () {
        $('p:first').addClass('intro note');
        /*      p      intro      , note      가      .*/
    });
});
</script>
</body>

```

Example

가 .

```

<head>
  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></scr
ipt>
  <style>
    .par_0 {
      color: blue;
    }
    .par_1 {
      color: red;
    }
  </style>
</head>
<body>
  <h1>This is a heading.</h1>

  <p>This is a paragraph</p>
  <!--      <p class="par_0">This is a paragraph</p>      -->
  <p>This is another paragraph</p>
  <!--      <p class="par_1">This is another paragraph</p>      -->

  <button>Add classes to p element</button>

  <script>
$(document).ready(function () {
    $('button').click(function () {
        $('p').addClass(function (n) {
            return 'par_' + n;

```

```
        /* n      p      . */  
    });  
});  
});  
</script>  
</body>
```

Example

addClass() removeClass()

가

```
<head>  
  <script  
src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></scr  
ipt>  
  <style>  
    .intro {  
      color: red;  
    }  
    .main {  
      background-color: yellow;  
    }  
  </style>  
</head>  
<body>  
  <h1>This is a heading</h1>  
  
  <p>This is another paragraph</p>  
  <p class="intro">This is a paragraph</p>  
  <!--           <p class="main">This is a paragraph</p>           .--->  
  <button>Change class name of the last p element</button>  
  
  <script>  
    $(document).ready(function () {  
      $('button').click(function () {  
        $('p:last').removeClass('intro').addClass('main');  
        /*      p      intro      , main      가 */  
      });  
    });  
  </script>  
</body>
```

, jQuery, addClass(), Method

From:
<https://125.132.25.164/dokuwiki/> -

. - 2023.12



Permanent link:
https://125.132.25.164/dokuwiki/doku.php?id=wiki:javascript:jquery:jquery_note:jquery_references_html_css:jquery_addclass_method

Last update: **2023/01/13 18:44**