

jQuery addClass() Method

- description : jQuery addClass() Method
- author :
- email : shlim@repia.com
- lastupdate : 2021-06-09

The source of this article

[jQuery addClass\(\) Method](#)

Example

<p> 가 .

```

<head>
  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></scr
ipt>
  <style>
    .intro {
      font-size: 150%;
      color: red;
    }
  </style>
</head>
<body>
  <h1>This is a heading.</h1>

  <p>This is a paragraph.</p>
  <!--           p           가   가
  <p class="intro">This is a paragraph.</p>           ,           .-->
  <p>This is another paragraph.</p>
  <button>Add a class name to the first p element</button>

  <script>
    $(document).ready(function () {
      $('button').click(function () {
        $('p:first').addClass('intro');
      });
    });
  </script>

```

</body>

Definition and Usage

`addClass()` is used to add one or more classes to the selected elements.

Tip: Use `toggleClass()` to toggle the class, (spaces).

Syntax

```
$(selector).addClass(classname, function(index, currentclass))
```

Parameter	Description
classname	One or more class names to be added to the selected elements.
function(index, currentclass)	Optional. A function to be executed for each element selected. The function receives two arguments: <code>index</code> - The index of the current element in the set of selected elements. <code>currentclass</code> - The current class of the element.

More Examples

Example

가 .

```
<head>
  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></scr
ipt>
  <style>
    .intro {
      font-size: 30px;
      color: blue;
    }
    .note {
      background-color: yellow;
    }
  </style>
</head>
<body>
  <h1>This is a heading</h1>
```

```

<p>This is a paragraph</p>
<!--      <p class="intro note">This is a paragraph</p>      p
intro class  note class가      . -->
<p>This is another paragraph</p>

<button>Add two class name to the first p element</button>

<script>
$(document).ready(function () {
    $('button').click(function () {
        $('p:first').addClass('intro note');
        /*      p      intro      , note      가      .*/
    });
});
</script>
</body>

```

Example

가 .

```

<head>
  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></scr
ipt>
  <style>
    .par_0 {
      color: blue;
    }
    .par_1 {
      color: red;
    }
  </style>
</head>
<body>
  <h1>This is a heading.</h1>

  <p>This is a paragraph</p>
  <!--      <p class="par_0">This is a paragraph</p>      -->
  <p>This is another paragraph</p>
  <!--      <p class="par_1">This is another paragraph</p>      -->

  <button>Add classes to p element</button>

  <script>
$(document).ready(function () {
    $('button').click(function () {
        $('p').addClass(function (n) {
            return 'par_' + n;
        });
    });
});

```

```
        /* n      p      . */
    });
    });
    });
</script>
</body>
```

Example

[addClass\(\)](#) [removeClass\(\)](#) ,

[가](#)

```
<head>
  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></scr
ipt>
  <style>
    .intro {
      color: red;
    }
    .main {
      background-color: yellow;
    }
  </style>
</head>
<body>
  <h1>This is a heading</h1>

  <p>This is another paragraph</p>
  <p class="intro">This is a paragraph</p>
  <!--      <p class="main">This is a paragraph</p>      .--->
  <button>Change class name of the last p element</button>

  <script>
    $(document).ready(function () {
      $('button').click(function () {
        $('p:last').removeClass('intro').addClass('main');
        /*      p      intro      , main      가 */
      });
    });
  </script>
</body>
```

[jQuery](#), [addClass\(\)](#), [Method](#)

From:
<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:

http://rwiki.repia.com/doku.php?id=wiki:javascript:jquery:jquery_note:jquery_references_html_css:jquery_addclass_method&rev=1623201304 

Last update: **2022/03/10 19:52**