

latin1 _utf8mb4 _

- description : Table Encoding
- author :
- email : hylee@repia.com
- lastupdate : 2020-04-22

(** DB Insert)

- ERROR 1366 (HY000) : incorrect string value : '\xED\x95\x9C\xEC\x9A\xB0...' for column 'ARTCL_HTML' at row 1

- 4byte CharacterSet 가

- mariaDB utf8 3byte utf8mb4
- (Character Set) (Encoding)

```
1. DB Character Set . (utf8mb4 )
2. DB dump .
3. mariaDB (, 가) .
4. dump DDL utf8mb4 utf8mb4 .
5. dump .
6. mariaDB DB .
```

1. Character Set

Table Caracter Set

```
SELECT CCSA.character_set_name FROM information_schema.`TABLES` T,
       information_schema.`COLLATION_CHARACTER_SET_APPLICABILITY` CCSA
WHERE
  CCSA.collation_name = T.table_collation
AND
  T.table_schema = "${Database name}"
AND
```

```
T.table_name = "${Table name}";
```

- MySQL database table character set

2. Database dump

```
[root@mysql ~]# mysqldump -uroot -p ${Database Name} -r ${Backup File Name}.sql
Password:
```

2-1. Dump File Encoding

- file -bi
- Dump utf8 DB utf9mb4

```
[root@mysql ~]# file -bi ${Backup File Name}.sql
```

3. mariaDB

가

* /etc/my.cnf

가

```
#
# This group is read both both by the client and the server
# use it for options that affect everything
#
[client-server]

#
# include all files from the config directory
#
[mysqld]
default_storage_engine=innodb
innodb_buffer_pool_size=445M
innodb_log_file_size=50M
max_connections = 10000
connect_timeout = 600
wait_timeout = 6000
max_allowed_packet = 2G
thread_cache_size = 128
sort_buffer_size = 4M
bulk_insert_buffer_size = 16M
tmp_table_size = 32M
max_heap_table_size = 32M
```

```

default_storage_engine = InnoDB
innodb_buffer_pool_size = 4G
innodb_log_buffer_size = 8M
innodb_file_per_table = 1
innodb_file_format = barracuda
innodb_open_files = 400
innodb_io_capacity = 400
innodb_flush_method = O_DIRECT

character-set-server=utf8mb4
collation-server=utf8mb4_general_ci

[client]
port=${Port}
default-character-set = utf8mb4

[mysqldump]
default-character-set = utf8mb4

[mysql]
default-character-set = utf8mb4

!includedir /etc/my.cnf.d

```

4. dump DDL

- Dump DDL 가 .

```

DROP TABLE IF EXISTS `${Table name}`;
/*!40101 SET @saved_cs_client = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;
CREATE TABLE `${Table name}` (
  `${column}` ${TYPE} NOT NULL,
  `${column}` ${TYPE} DEFAULT NULL,
  `${column}` ${TYPE} DEFAULT NULL,
  `${column}` ${TYPE} DEFAULT NULL,
  `${column}` ${TYPE} DEFAULT NULL,
  PRIMARY KEY (${COLUMN})
) ENGINE=InnoDB DEFAULT CHARSET=utf8;

```

- DDL “CHARSET=utf8;”가 “CHARSET=utf8mb4;”

Ref

- (Character Set) (Encoding)
[, java, List](#)

From:
<http://rwiki.repia.com/> - . - 2023.12

Permanent link:
http://rwiki.repia.com/doku.php?id=wiki:mariadb:latin1%EC%97%90%EC%84%9C_utf8mb4%EB%A1%9C_%EB%B3%80%ED%99%98%ED%95%98%EA%B8%B0&rev=1587520431 

Last update: **2022/03/10 19:52**