

- description :
- author :
- email : kimmk@repia.com
- lastupdate : 2020-03-10

ls

```
[www@www tmp]$ ls -alhS | more
```

option
a : all
l : long format
h : human reading (K, M, G)
S : sort by Size, t : sort by Time

find

'_header.txt'

```
[www@www tmp]$ find ./ -type 'd' -ls -exec cp ./_header.txt {} \;
```

가 0 가

```
[www@www tmp]$ find ./ -type 'f' -size 0 -ls
```

or

```
[www@www tmp]$ find ./ -type 'f' -empty
```

가 0

```
[www@www tmp]$ find ./ -type f -size 0 -exec rm -f {} \;
```

or

```
[www@www tmp]$ find ./ -type f -size 0 | xargs rm -f
```

or

```
[www@www tmp]$ find ./ -type f -size 0 -delete
```

du

```
[www@www tmp]$ du | sort -nr
```

sed

```
[www@www tmp]$ sed -i 's|/hello/|/Hello Word|g' *.conf
```

/hello , /Hello Word , *.conf ↗ conf

crontab

```
[www@www tmp]$ crontab -e
#Repli_Search_RealRank
0,10,20,30,40,50 8-20 * * * /opt/search/RSA/bin/realRank.sh
0 7 * * * /opt/search/RSA/bin/acsctl.sh restart
#root
0,10,20,30,40,50 8-20 * * * su - search -c /opt/search/RSA/bin/realRank.sh
0 7 * * * su - search -c /opt/search/RSA/bin/acsctl.sh restart
```

-e , -l
www crontab -e www .

crontab

* * * * * * * * * *
(0-59) (0-23) (1-31) (1-12) (0-7)

- (Linux Crontab)

tar

-

```
[www@www tmp]$ tar fcvh search.tar.gz search
```

f: tar , c: tar , z: gzip , v: View , h()
) : ↗

- - (, , , , ...)

```
[www@www tmp]$ tar tvfz archive.tar.gz
```

t: tar List , v: , f: , z:

-

```
[www@www tmp]$ tar xvfz archive.tar.gz /
```

/ , tar tvfz .

Ref

- How can I sort du -h output by size

, ls, find, seq, crontab, tar

From: <http://rwiki.repia.com/> - . - 2023.12
Permanent link: http://rwiki.repia.com/doku.php?id=wiki:os:linux:%EB%A6%AC%EB%88%85%EC%8A%A4%EC%97%90%EC%84%9C_%EC%9E%90%EC%A3%BC_%EC%82%AC%EC%9A%A9%ED%95%98%EB%8A%94_%EB%AA%85%EB%A0%B9%EC%96%B4&rev=1589165999
Last update: 2022/03/10 19:52

