

bashrc

- description :
- author :
- email : dhan@repia.com
- lastupdate : 2020-01-31

Environment()

```
#  
D_YMD=`date +%Y%m%d`  
D_Y-M-D=`date +%Y-%m-%d`  
#  
TMOUT=0  
export TMOUT D_YMD D_Y-M-D
```

export 가

Alias

```
alias rlog='tail -n200 -f ${RSA_ROOT}/logs/javaLog/log_${D_YMD}.txt'  
alias tlog='tail -n200 -f ${TOMCAT_ROOT}/logs/localhost.${D_Y-M-D}.log'  
alias search='cd ${RSA_ROOT}/bin'  
alias sfront='cd ${RSA_ROOT}/bin/html'
```

```
$> source ~/.bashrc  
or  
$> . ~/.bashrc
```

Example

```
# .bashrc  
  
# User specific aliases and functions  
  
alias rm='rm -i'  
alias cp='cp -i'  
alias mv='mv -i'  
HADOOP_INSTALL=/usr/local/hadoop-1.0.3  
PATH=$PATH:$HADOOP_INSTALL/bin
```

```
# Source global definitions
if [ -f /etc/bashrc ]; then
    . /etc/bashrc
fi
```

Ref

, [bash](#), [bashrc](#)

From:

<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:

<http://rwiki.repia.com/doku.php?id=wiki:os:linux:bashrc&rev=1580468703>



Last update: **2022/03/10 19:52**