

bashrc

- description :
- author :
- email : dhan@repia.com
- lastupdate : 2020-01-31

Environment()

```
# date
D_YMD=`date +%Y%m%d`
D_Y-M-D=`date +%Y-%m-%d`
#
TMOUT=0
export TMOUT D_YMD D_Y-M-D
```

export	date	Value	가	!!

Alias

```
alias rlog='tail -n200 -f ${RSA_ROOT}/logs/javaLog/log_${D_YMD}.txt'
alias tlog='tail -n200 -f ${TOMCAT_ROOT}/logs/localhost.${D_Y-M-D}.log'
alias search='cd ${RSA_ROOT}/bin'
alias sfront='cd ${RSA_ROOT}/bin/html'
```

Shell

```
$> source ~/.bashrc
or
$> . ~/.bashrc
```

Example

```
# .bashrc

# User specific aliases and functions

alias rm='rm -i'
alias cp='cp -i'
```

```
alias mv='mv -i'
HADOOP_INSTALL=/usr/local/hadoop-1.0.3
PATH=$PATH:$HADOOP_INSTALL/bin

# Source global definitions
if [ -f /etc/bashrc ]; then
    . /etc/bashrc
fi
```

Ref

, [bash](#), [bashrc](#)

From:

<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:

<http://rwiki.repia.com/doku.php?id=wiki:os:linux:bashrc&rev=1580469044>



Last update: **2022/03/10 19:52**