

Mybatis() ,

- description :
- author :
- email : dhan@repia.com
- lastupdate : 2020-01-31

mapper.xml

SELECT

```
<SELECT id="boardList" resultType="BoardDto" useCache="true">
    SELECT * FROM tbl_board ORDER BY pos ASC
</select>
```

resultType .

UPDATE

```
<update id="readCount" parameterType="int">
    update tbl_board set count = count + 1 where seq = #{seq}
</update>
```

parameterType .

DELETE

```
<DELETE id="deleteBoard" parameterType="map">
    DELETE FROM tbl_board WHERE seq=#{seq} AND password=#{storPass}
</delete>
```

parameterType .

MYBATIS DB

INSERT

```
<INSERT id="insertStudents" useGeneratedKeys="true" keyProperty="id"
parameterType="Student">
    INSERT INTO Students ( name, email )
    VALUES ( #{name}, #{email} )
</insert>
```

selectKey 가

```
<INSERT id="insertStudents" parameterType="Student">
  <selectKey keyProperty="id" resultType="int" ORDER="BEFORE">
    SELECT SEQ_ID.nextval FROM DUAL
  </selectKey>
  INSERT INTO Students
  (id, name , email)
  VALUES
  ({id}, #{name}, #{email})
</insert>
```

Mapper XML

mybatis insert/update

가

Mybatis Null (ibatis)

Mybatis

```
<IF test="stringProperty != null">
</if>
```

ibatis

```
<isNotNull property="stringProperty">
</isNotNull>
```

Mybatis Tip

- DBCP

```
<property name="initialSize" value="0"/>
```

```
<property name="maxActive" value="8"/>
<property name="maxIdle" value="8"/>
<property name="minIdle" value="0"/>
<property name="maxWait" value="-1"/>
```

initialSize:

0

maxActive:

8

maxWait

maxIdle:

8

maxActive가 10 , maxIdle 8 10

가

```

, maxIdle      8 가
minIdle:      8
              0
              가
              가 minIdle
maxWait -      가
              가
-1      -1

```

Ref

- [myBatis parameterType="String"](#)
- [- dataSource \(DBCP\)](#)
- [, mybatis](#)

From:
<http://rwiki.repia.com/> -
 2023.12

Permanent link:
<http://rwiki.repia.com/doku.php?id=wiki:spring:mybatis&rev=1584612707>

Last update: **2022/03/10 19:52**

