

Mybatis() ,

- description :
- author :
- email : dhan@repia.com
- lastupdate : 2020-01-31

mapper.xml

SELECT

```
<SELECT id="boardList" resultType="BoardDto" useCache="true">
    SELECT * FROM tbl_board ORDER BY pos ASC
</select>
```

resultType .

UPDATE

```
<update id="readCount" parameterType="int">
    update tbl_board set count = count + 1 where seq = #{seq}
</update>
```

parameterType .

DELETE

```
<DELETE id="deleteBoard" parameterType="map">
    DELETE FROM tbl_board WHERE seq=#{seq} AND password=#{storPass}
</delete>
```

parameterType .

MYBATIS DB

INSERT

```
<INSERT id="insertStudents" useGeneratedKeys="true" keyProperty="id"
parameterType="Student">
    INSERT INTO Students ( name, email )
    VALUES ( #{name}, #{email} )
</insert>
```

selectKey 가

```

<INSERT id="insertStudents" parameterType="Student">
  <selectKey keyProperty="id" resultType="int" ORDER="BEFORE">
    SELECT SEQ_ID.nexyval FROM DUAL
  </selectKey>
  INSERT INTO Students
  (id, name , email)
  VALUES
  ({id}, {name}, {email})
</insert>

```

Mapper XML

mybatis insert/update

가

Mybatis Null (ibatis)

Mybatis

```

<if test="stringProperty != null">
</if>

```

ibatis

```

<isNotNull property="stringProperty">
</isNotNull>

```

mybatis ibatis

Mybatis Tip

- DBCP

<property name="initialSize" value="0"/>

```

<property name="maxActive" value="8"/>
<property name="maxIdle" value="8"/>
<property name="minIdle" value="0"/>
<property name="maxWait" value="-1"/>

```

initialSize:

0

maxActive:

8

maxWait

maxIdle:

maxActive가 10⁸ , maxIdle 8 10 가 .
 , maxIdle 8 가 .
 minIdle: . 0 .
 가 ,
 가 minIdle minIdle
 maxWait - 가 .
 가 . -1 .
 -1 .

Ref

- [myBatis parameterType="String"](#)
 - [- dataSource \(DBCP\)](#)
- , [eleven](#), [mybatis](#)

From:

<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:

<http://rwiki.repia.com/doku.php?id=wiki:spring:mybatis&rev=1585055743>



Last update: **2022/03/10 19:52**