

<http://temp.repia.com/dhan/openapiclient-0.0.1-SNAPSHOT.jar.gz>

```
TB_ORGAN
CREATE CACHED TABLE "PUBLIC"."TB_ORGAN" (
  "OFCFS_CODE" VARCHAR(16),
  "OFCPS_NM" VARCHAR(100),
  "DEPT_CODE" VARCHAR(16),
  "DEPT_NM" VARCHAR(100),
  "USER_NM" VARCHAR(100),
  "OFFM_TELNO" VARCHAR(32),
  "EMAIL" VARCHAR(100),
  "JOB_DC" CLOB,
  "ORDR" NUMBER
);
```

```
java -Dlogback.configurationFile=resources/logback.xml -cp ../resources/ -
jar openapiclient-0.0.1-SNAPSHOT.jar HRD ORGAN refresh
```

```
#-----
#  api.properties :
#-----
#  1.  key = value
#  2.  key          가, value          가
#  3.  key          가,   value        가
#  4.          가   '\'   가(   '\'   '\'
```

```
database.type=h2
database.driver=org.h2.Driver
database.jdbcurl=jdbc:h2:tcp://127.0.0.1:9092/~/.rsa41
database.user=sa
database.password=fpvldk!@#

ORGAN.table=TB_ORGAN
```

```
logback.xml
<?xml version="1.0" encoding="UTF-8"?>
<!--
  [Layout]
  %m :
  %p : trace > debug > info > warn > error      priority
  %r :          가
  %c :  )          가 a.b.c          %c{2}   b.c가          .
  %n :          가          .  \r\n          \n
  %d :          가          (          .)
```

```

) %d{HH:mm:ss} %d{dd MMMM yyyy HH:mm:ss}
%C :
) 가 org.apache.xyz.SomeClass %C{2} xyz.SomeClass 가

%M : method
%F :
%l : caller
%L : caller
%X : thread NDC(nested diagnostic context)
%X : thread MDC(mapped diagnostic context)
%% : %
%t : 가
-->

```

```

<configuration scan="true" scanPeriod="30 seconds">
  <appender name="ROLLING"
class="ch.qos.logback.core.rolling.RollingFileAppender">
    <rollingPolicy
class="ch.qos.logback.core.rolling.TimeBasedRollingPolicy">
      <!-- rollover daily -->
      <fileNamePattern>logs/openapiclient-%d{yyyy-MM-
dd}.%i.log.zip</fileNamePattern>
      <timeBasedFileNamingAndTriggeringPolicy
class="ch.qos.logback.core.rolling.SizeAndTimeBasedFNATP">
        <!-- or whenever the file size reaches 100MB -->
        <maxFileSize>100MB</maxFileSize>
      </timeBasedFileNamingAndTriggeringPolicy>
    </rollingPolicy>
    <encoder>
      <pattern>%d{HH:mm:ss.SSS} %-5level %logger{36} -
%msg%n</pattern>
    </encoder>
  </appender>
  <appender name="STDOUT" class="ch.qos.logback.core.ConsoleAppender">
    <layout class="ch.qos.logback.classic.PatternLayout">
      <Pattern>%d{HH:mm:ss.SSS} [%-5level] - %msg%n</Pattern>
    </layout>
  </appender>

  <!-- Loggers -->
  <logger name="org.apache.catalina" level="ERROR">
</logger>

  <logger name="org.apache.commons" level="ERROR">
</logger>

  <logger name="org.springframework" level="DEBUG" >
</logger>

  <logger name="java.sql" level="DEBUG">
</logger>

```

```
<logger name="org.mybatis.spring" level="DEBUG">
</logger>

<root level="ERROR">
  <appender-ref ref="ROLLING"/>
  <appender-ref ref="STDOUT" />
</root>
</configuration>
```

From:

<http://rwiki.repia.com/> -

. - 2023.12

Permanent link:

<http://rwiki.repia.com/doku.php?id=wiki:user:dhan:temp&rev=1630414443>



Last update: **2022/03/10 19:52**